

Page 1 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.06.2018 / 0005
Replacing version dated / version: 30.05.2016 / 0004
Valid from: 12.06.2018
PDF print date: 15.06.2018
3-IN-ONE® Anti-Seize Copper Grease

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

3-IN-ONE® Anti-Seize Copper Grease

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

WD-40 Company Limited, PO Box 440, Kiln Farm, Milton Keynes, MK11 3LF, United Kingdom
Phone:+44 (0) 1908 555400, Fax:+44 (0) 1908 266900
Compliance@wd40.co.uk, www.wd40.co.uk

(IRL)

P.R. Rielly Limited KarKraft House, Kilbarrack Industrial Estate, Kilbarrack, Dublin 5, Ireland
Phone:01-832 0006, Fax:01-832 0016
web@team.ie

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

(IRL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:
+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)
+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (WDC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|-----------------|-----------------|---|
| Skin Irrit. | 2 | H315-Causes skin irritation. |
| Asp. Tox. | 1 | H304-May be fatal if swallowed and enters airways. |
| Aquatic Chronic | 3 | H412-Harmful to aquatic life with long lasting effects. |
| Aerosol | 1 | H222-Extremely flammable aerosol. |
| Aerosol | 1 | H229-Pressurised container: May burst if heated. |

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.06.2018 / 0005

Replacing version dated / version: 30.05.2016 / 0004

Valid from: 12.06.2018

PDF print date: 15.06.2018

3-IN-ONE® Anti-Seize Copper Grease



Danger

H315-Causes skin irritation. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P273-Avoid release to the environment. P280-Wear protective gloves.

P332+P313-If skin irritation occurs: Get medical advice / attention.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container safely.

Without adequate ventilation, formation of explosive mixtures may be possible.

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substance

n.a.

3.2 Mixture

| | |
|---|--|
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | |
| Registration number (REACH) | 01-2119475514-35-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP | 921-024-6 (REACH-IT List-No.) |
| CAS | --- |
| content % | 10-<20 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Aquatic Chronic 2, H411 Asp. Tox. 1, H304 STOT SE 3, H336 |
| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics | |
| Registration number (REACH) | 01-2119475515-33-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP | 927-510-4 (REACH-IT List-No.) |
| CAS | --- |
| content % | 5-10 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411 |

Page 3 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.06.2018 / 0005
 Replacing version dated / version: 30.05.2016 / 0004
 Valid from: 12.06.2018
 PDF print date: 15.06.2018
 3-IN-ONE® Anti-Seize Copper Grease

| | |
|--|--|
| Hydrocarbons, C6, isoalkanes, <5% n-hexane | |
| Registration number (REACH) | 01-2119484651-34-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP | 931-254-9 (REACH-IT List-No.) |
| CAS | (64742-49-0) |
| content % | 5-10 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411 |

| | |
|--|--|
| Copper | |
| Registration number (REACH) | --- |
| Index | --- |
| EINECS, ELINCS, NLP | 231-159-6 |
| CAS | 7440-50-8 |
| content % | 0,5-5 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Acute Tox. 4, H302 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411 |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.
 If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.
 Rinse the mouth thoroughly with water.
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.
 Danger of aspiration
 In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes
 Irritation of the respiratory tract
 Coughing
 Headaches
 Dizziness
 Effects/damages the central nervous system
 Unconsciousness
 With long-term contact:
 Drying of the skin.
 Dermatitis (skin inflammation)
 Ingestion:
 Nausea
 Vomiting

Danger of aspiration

Oedema of the lungs

chemical pneumonitis (condition similar to pneumonia)

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

Pulmonary oedema prophylaxis

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Exinction powder

Water jet spray

Alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Without adequate ventilation, formation of explosive mixtures may be possible.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Page 5 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.06.2018 / 0005
 Replacing version dated / version: 30.05.2016 / 0004
 Valid from: 12.06.2018
 PDF print date: 15.06.2018
 3-IN-ONE® Anti-Seize Copper Grease

Take measures against electrostatic charging, if appropriate.
 Do not use on hot surfaces.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Do not store with flammable or self-igniting materials.
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Keep protected from direct sunlight and temperatures over 50°C.
 Store in a well ventilated place.
 Store cool.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 1000 mg/m3

| Chemical Name | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | Content %:10- <20 |
|------------------------|---|-------------------|
| WEL-TWA: 1400 mg/m3 | WEL-STEL: --- | --- |
| Monitoring procedures: | - Compur - KITA-187 S (551 174) | |
| BMGV: --- | Other information: (WEL acc. to RCP-method, EH40) | |

| Chemical Name | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | Content %:10- <20 |
|---|---|-------------------|
| OELV-8h: 400 ppm (1590 mg/m3) (naphtha) | OELV-15min: --- | --- |
| Monitoring procedures: | - Compur - KITA-187 S (551 174) | |
| BLV: --- | Other information: --- | |

| Chemical Name | Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics | Content %:5-10 |
|------------------------|--|----------------|
| WEL-TWA: 800 mg/m3 | WEL-STEL: --- | --- |
| Monitoring procedures: | - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) | |
| BMGV: --- | Other information: (WEL acc. to RCP-method, EH40) | |

| Chemical Name | Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics | Content %:5-10 |
|---------------------------|--|----------------|
| OELV-8h: 1200 mg/m3 (AGW) | OELV-15min: 2(II) (AGW) | --- |
| Monitoring procedures: | - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) | |
| BLV: --- | Other information: --- | |

| Chemical Name | Hydrocarbons, C6, isoalkanes, <5% n-hexane | Content %:5-10 |
|------------------------|--|----------------|
| WEL-TWA: 800 mg/m3 | WEL-STEL: --- | --- |
| Monitoring procedures: | - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) | |
| BMGV: --- | Other information: (WEL acc. to RCP-method, EH40) | |

| Chemical Name | Hydrocarbons, C6, isoalkanes, <5% n-hexane | Content %:5-10 |
|---------------------------|--|----------------|
| OELV-8h: 1200 mg/m3 (AGW) | OELV-15min: 2(II) (AGW) | --- |

Page 6 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.06.2018 / 0005
 Replacing version dated / version: 30.05.2016 / 0004
 Valid from: 12.06.2018
 PDF print date: 15.06.2018
 3-IN-ONE® Anti-Seize Copper Grease

| | |
|------------------------|--|
| Monitoring procedures: | - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) |
|------------------------|--|

| | |
|----------|------------------------|
| BLV: --- | Other information: --- |
|----------|------------------------|

| GB Chemical Name | Copper | Content %:0,5-5 |
|------------------|--------|-----------------|
|------------------|--------|-----------------|

| | | |
|---|--|-----|
| WEL-TWA: 1 mg/m3 (dusts and mists, as Cu) | WEL-STEL: 2 mg/m3 (dusts and mists, as Cu) | --- |
|---|--|-----|

| | |
|------------------------|---|
| Monitoring procedures: | ISO 15202 (Workplace air - Determination of metals and metalloids in airborne particulate matter by Inductively Coupled Plasma Atomic Emission Spectrometry), Part 1-3 - 2000(Part 1), 2001(Part 2), 2004 (Part 3) - EU project BC/CEN/ENTR/000/2002-16 card 84-1 (2004) - MDHS 91 (Metals and metalloids in workplace air by X-ray fluorescence spectrometry) - 1998 - EU project BC/CEN/ENTR/000/2002-16 card 84-2 (2004) - NIOSH 7029 (Copper (dust and fume)) - 1994 - NIOSH 7300 (Elements by ICP (nitric/perchloric ashing)) - 2003 - NIOSH 7301 (Elements by ICP (aqua regia ashing)) - 2003 - NIOSH 7303 (Elements by ICP (Hot block HCl/HNO3 digestion)) - 2003 OSHA ID-121 (Metal and metalloid particulates in workplace atmospheres (Atomic absorption)) - 2002 - EU project BC/CEN/ENTR/000/2002-16 card 84-10 (2004) - OSHA ID-125G (Metal and metalloid particulates in workplace atmospheres (ICP)) - 2002 OSHA ID-206 (ICP analysis of metal/metalloid particulates from solder operations) - 1991 |
|------------------------|---|

| | |
|-----------|------------------------|
| BMGV: --- | Other information: --- |
|-----------|------------------------|

| IRL Chemical Name | Copper | Content %:0,5-5 |
|-------------------|--------|-----------------|
|-------------------|--------|-----------------|

| | | |
|---------------------------------|------------------------------------|-----|
| OELV-8h: 1 mg/m3 (dust + mists) | OELV-15min: 2 mg/m3 (dust + mists) | --- |
|---------------------------------|------------------------------------|-----|

| | |
|------------------------|---|
| Monitoring procedures: | ISO 15202 (Workplace air - Determination of metals and metalloids in airborne particulate matter by Inductively Coupled Plasma Atomic Emission Spectrometry), Part 1-3 - 2000(Part 1), 2001(Part 2), 2004 (Part 3) - EU project BC/CEN/ENTR/000/2002-16 card 84-1 (2004) - MDHS 91 (Metals and metalloids in workplace air by X-ray fluorescence spectrometry) - 1998 - EU project BC/CEN/ENTR/000/2002-16 card 84-2 (2004) - NIOSH 7029 (Copper (dust and fume)) - 1994 - NIOSH 7300 (Elements by ICP (nitric/perchloric ashing)) - 2003 - NIOSH 7301 (Elements by ICP (aqua regia ashing)) - 2003 - NIOSH 7303 (Elements by ICP (Hot block HCl/HNO3 digestion)) - 2003 OSHA ID-121 (Metal and metalloid particulates in workplace atmospheres (Atomic absorption)) - 2002 - EU project BC/CEN/ENTR/000/2002-16 card 84-10 (2004) - OSHA ID-125G (Metal and metalloid particulates in workplace atmospheres (ICP)) - 2002 OSHA ID-206 (ICP analysis of metal/metalloid particulates from solder operations) - 1991 |
|------------------------|---|

| | |
|----------|------------------------|
| BLV: --- | Other information: --- |
|----------|------------------------|

| GB Chemical Name | Petroleum gases, liquified | Content %: |
|------------------|----------------------------|------------|
|------------------|----------------------------|------------|

| | | |
|--|---|-----|
| WEL-TWA: 1000 ppm (1750 mg/m3) (Liquefied petroleum gas (LPG)) | WEL-STEL: 1250 ppm (2180 mg/m3) (Liquefied petroleum gas (LPG)) | --- |
|--|---|-----|

| | |
|------------------------|-----|
| Monitoring procedures: | --- |
|------------------------|-----|

| | |
|-----------|------------------------|
| BMGV: --- | Other information: --- |
|-----------|------------------------|

| IRL Chemical Name | Petroleum gases, liquified | Content %: |
|-------------------|----------------------------|------------|
|-------------------|----------------------------|------------|

| | | |
|--------------------------------|-----------------------------------|-----|
| OELV-8h: 1000 ppm (1800 mg/m3) | OELV-15min: 1250 ppm (2250 mg/m3) | --- |
|--------------------------------|-----------------------------------|-----|

| | |
|------------------------|-----|
| Monitoring procedures: | --- |
|------------------------|-----|

| | |
|----------|------------------------|
| BLV: --- | Other information: --- |
|----------|------------------------|

| GB Chemical Name | Oil mist, mineral | Content %: |
|------------------|-------------------|------------|
|------------------|-------------------|------------|

| | | |
|--------------------------|----------------------------|-----|
| WEL-TWA: 5 mg/m3 (ACGIH) | WEL-STEL: 10 mg/m3 (ACGIH) | --- |
|--------------------------|----------------------------|-----|

| | |
|------------------------|--|
| Monitoring procedures: | - Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031) |
|------------------------|--|

| | |
|-----------|------------------------|
| BMGV: --- | Other information: --- |
|-----------|------------------------|

| IRL Chemical Name | Oil mist, mineral | Content %: |
|-------------------|-------------------|------------|
|-------------------|-------------------|------------|

| | | |
|---|-----------------|-----|
| OELV-8h: 5 mg/m3 (Mineral oil, pure, highly & severely refined (inhalable)) | OELV-15min: --- | --- |
|---|-----------------|-----|

| | |
|------------------------|--|
| Monitoring procedures: | - Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031) |
|------------------------|--|

| | |
|----------|------------------------|
| BLV: --- | Other information: --- |
|----------|------------------------|

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BLV = Biological limit value | Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

8.2 Exposure controls

| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | | | | | | |
|---|--|------------------------------|------------|-------|--------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 699 | mg/kg bw/day | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 699 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 608 | mg/kg bw/day | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 773 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Short term, systemic effects | DNEL | 2035 | mg/kg bw/day | |

| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics | | | | | | |
|--|--|-----------------------------|------------|-------|--------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 149 | mg/kg bw/day | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 149 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 447 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 300 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 2085 | mg/m3 | |

| Hydrocarbons, C6, isoalkanes, <5% n-hexane | | | | | | |
|--|--|-----------------------------|------------|-------|--------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 1301 | mg/kg bw/day | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 1377 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 1131 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 13964 | mg/kg bw/day | |

| | | | | | | |
|---------------------|--------------------|-----------------------------|------|------|-------|--|
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 5306 | mg/m3 | |
|---------------------|--------------------|-----------------------------|------|------|-------|--|

| Copper | | | | | | |
|---------------------|--|------------------|------------|-------|------------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 7,8 | µg/l | |
| | Environment - marine | | PNEC | 5,2 | µg/l | |
| | Environment - sediment, freshwater | | PNEC | 87 | mg/kg dry weight | |
| | Environment - sediment, marine | | PNEC | 676 | mg/kg dry weight | |
| | Environment - soil | | PNEC | 65,5 | mg/kg dry weight | |
| | Environment - sewage treatment plant | | PNEC | 230 | µg/l | |

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Normally not necessary.

with long-term contact:

If applicable

Protective nitrile gloves (EN 374)

Protective gloves made of polyvinyl alcohol (EN 374)

Protective Viton® / fluoroelastomer gloves (EN 374)

Minimum layer thickness in mm:

>= 0,4

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Page 9 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.06.2018 / 0005
 Replacing version dated / version: 30.05.2016 / 0004
 Valid from: 12.06.2018
 PDF print date: 15.06.2018
 3-IN-ONE® Anti-Seize Copper Grease

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|------------------------------------|
| Physical state: | Aerosol. Active substance: liquid. |
| Colour: | Copper |
| Odour: | Characteristic |
| Odour threshold: | Not determined |
| pH-value: | n.a. |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | n.a. |
| Flash point: | n.a. |
| Evaporation rate: | Not determined |
| Flammability (solid, gas): | Not determined |
| Lower explosive limit: | 0,8 Vol-% |
| Upper explosive limit: | 9,0 Vol-% |
| Vapour pressure: | Not determined |
| Vapour density (air = 1): | Not determined |
| Density: | Not determined |
| Bulk density: | Not determined |
| Solubility(ies): | Not determined |
| Water solubility: | Insoluble |
| Partition coefficient (n-octanol/water): | Not determined |
| Auto-ignition temperature: | Not determined |
| Decomposition temperature: | Not determined |
| Viscosity: | Not determined |
| Explosive properties: | Not determined |
| Oxidising properties: | No |

9.2 Other information

| | |
|---------------------------|----------------|
| Miscibility: | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity: | Not determined |
| Surface tension: | Not determined |
| Solvents content: | Not determined |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.06.2018 / 0005

Replacing version dated / version: 30.05.2016 / 0004

Valid from: 12.06.2018

PDF print date: 15.06.2018

3-IN-ONE® Anti-Seize Copper Grease

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

| 3-IN-ONE® Anti-Seize Copper Grease | | | | | | |
|---|----------|-------|-------|----------|-------------|------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | ATE | >2000 | mg/kg | | | calculated value |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics | | | | | | |
|--|----------|-------|---------|----------|--|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >2000 | mg/kg | Rat | | |
| Acute toxicity, by oral route: | LD50 | >8 | ml/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | >=4 | ml/kg | Rat | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >23,3 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Irritant |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | diarrhoea, headaches, dizziness, nausea and vomiting. |

| Hydrocarbons, C6, isoalkanes, <5% n-hexane | | | | | | |
|--|----------|--------|-------|----------|--|-------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >16750 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >3350 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | 259354 | mg/m3 | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | | | Irritant |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | No (skin contact) |
| Aspiration hazard: | | | | | | Yes |

Page 11 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.06.2018 / 0005
 Replacing version dated / version: 30.05.2016 / 0004
 Valid from: 12.06.2018
 PDF print date: 15.06.2018
 3-IN-ONE® Anti-Seize Copper Grease

| | | | | | | |
|-----------|--|--|--|--|--|--|
| Symptoms: | | | | | | drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting. |
|-----------|--|--|--|--|--|--|

| Petroleum gases, liquified | | | | | | |
|--------------------------------|----------|-------|------|----------|-------------|-------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by inhalation: | LC50 | >5 | mg/l | | | |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| 3-IN-ONE® Anti-Seize Copper Grease | | | | | | | |
|--|----------|------|-------|------|----------|-------------|--|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | Isolate as much as possible with an oil separator. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Other adverse effects: | | | | | | | n.d.a. |
| Other information: | | | | | | | According to the recipe, contains no AOX. |

| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics | | | | | | | |
|--|----------|------|-------|------|---------------------------------|--|-------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >13,4 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EL50 | 24h | 12 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | 3 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EL50 | 72h | 12 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |

| Hydrocarbons, C6, isoalkanes, <5% n-hexane | | | | | | | |
|--|----------|------|-------|------|----------|-------------|-------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |

Page 12 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 12.06.2018 / 0005
 Replacing version dated / version: 30.05.2016 / 0004
 Valid from: 12.06.2018
 PDF print date: 15.06.2018
 3-IN-ONE® Anti-Seize Copper Grease

| | | | | | | | |
|--|-----------|-----|-------|------|---------------------------------|------|--|
| 12.1. Toxicity to fish: | LC50 | 48h | >1 | mg/l | Oryzias latipes | | Analogous conclusion |
| 12.1. Toxicity to fish: | NOEC/NOEL | 28d | 4,09 | mg/l | Oncorhynchus mykiss | QSAR | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 31,9 | mg/l | Daphnia magna | QSAR | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | 7,14 | mg/l | Daphnia magna | QSAR | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | 3,87 | mg/l | Daphnia magna | | Analogous conclusion |
| 12.1. Toxicity to algae: | NOELR | 72h | 30 | mg/l | Raphidocelis subcapitata | | |
| 12.1. Toxicity to algae: | ErC50 | 72h | 55 | mg/l | Pseudokirchneriella subcapitata | | Analogous conclusion |
| 12.1. Toxicity to algae: | EC50 | 72h | 13,56 | mg/l | Pseudokirchneriella subcapitata | QSAR | |
| 12.2. Persistence and degradability: | | 28d | 98 | % | | | Readily biodegradable (Analogous conclusion) |
| 12.3. Bioaccumulative potential: | Log Kow | | 4 | | | | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

Petroleum gases, liquified

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|-------------------------|----------|------|--------|------|----------|-------------|-------|
| 12.1. Toxicity to fish: | LC50 | 96h | 147,54 | mg/l | | QSAR | |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 04 other organic solvents, washing liquids and mother liquors

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F

LQ: 1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.06.2018 / 0005

Replacing version dated / version: 30.05.2016 / 0004

Valid from: 12.06.2018

PDF print date: 15.06.2018

3-IN-ONE® Anti-Seize Copper Grease

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2.1



14.4. Packing group:

-

EmS:

F-D, S-U

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):

2.1



14.4. Packing group:

-

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

| Hazard categories | Notes to Annex I | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements |
|-------------------|------------------|---|---|
| P3a | 11.1 | 150 (netto) | 500 (netto) |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

65 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

EU F0008

Revised sections:

2, 3, 8, 11, 12, 15

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.06.2018 / 0005

Replacing version dated / version: 30.05.2016 / 0004

Valid from: 12.06.2018

PDF print date: 15.06.2018

3-IN-ONE® Anti-Seize Copper Grease

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|---|
| Skin Irrit. 2, H315 | Classification according to calculation procedure. |
| Asp. Tox. 1, H304 | Classification according to calculation procedure. |
| Aquatic Chronic 3, H412 | Classification according to calculation procedure. |
| Aerosol 1, H222 | Classification according to calculation procedure. |
| Aerosol 1, H229 | Classification based on the form or physical state. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation

Asp. Tox. — Aspiration hazard

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Acute Tox. — Acute toxicity - oral

Aquatic Acute — Hazardous to the aquatic environment - acute

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

Page 16 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 12.06.2018 / 0005

Replacing version dated / version: 30.05.2016 / 0004

Valid from: 12.06.2018

PDF print date: 15.06.2018

3-IN-ONE® Anti-Seize Copper Grease

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.