

Page: 1

Compilation date: 20/5/14

Revision No: 5

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 206 STRIKE RELEASE OIL

Product code: STRIKE - ALL SIZES

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	EVERBUILD BUILDING PRODUCTS LTD
	SITE 41, KNOWSTHORPE WAY
	CROSS GREEN INDUSTRIAL ESTATE
	LEEDS
	WEST YORKSHIRE
	LS9OSW
	ENGLAND
Tel:	0044 113 240 3456
Fax:	0044 113 240 0024
Email:	pault@everbuild.co.uk
	•

1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP:	-: R10; N: R51/53; Xn: R65
Classification under CLP:	Asp. Tox. 1: H304; Flam. Liq. 3: H226
Most important adverse effects:	Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the
	aquatic environment. Harmful: may cause lung damage if swallowed.

2.2. Label elements

Label elements under CLP:		
Hazard statements:	H226: Flammable liquid and vapour.	
	H304: May be fatal if swallowed and enters airways.	
Signal words:	Danger	
Hazard pictograms:	GHS02: Flame	
	GHS08: Health hazard	

206 STRIKE RELEASE OIL

Precautionary statements:	P103: Read label before use.	
	P210: Keep away from heat/sparks/open flames/hot surfaces No smoking.	
	P102: Keep out of reach of children.	
	P243: Take precautionary measures against static discharge.	
	P233: Keep container tightly closed.	
	P242: Use only non-sparking tools.	
	P280: Wear protective gloves/protective clothing/eye protection/face protection.	
	P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.	
	P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.	
	Rinse skin with water/shower.	
	P331: Do NOT induce vomiting.	
	P370+378: In case of fire: Use chemical powder, alcohol resistant foam or carbon	
	dioxide for extinction.	
	P405: Store locked up.	
	P501: Dispose of contents to In accordance with local legislation.	
	P403+235: Store in a well-ventilated place. Keep cool.	
Label elements under CHIP:		
Hazard symbols:	Harmful.	
	Dangerous for the environment.	
Risk phrases:	R10: Flammable.	
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic	
	environment.	
	R65: Harmful: may cause lung damage if swallowed.	
Safety phrases:	S2: Keep out of the reach of children.	
	S23: Do not breathe vapour.	
	S24: Avoid contact with skin.	
	S62: If swallowed, do not induce vomiting: seek medical advice immediately and show	
	this container or label.	
2.3. Other hazards		
Other hazards:	Product is not classified as flammable (R10) due to flashpoint >61`C. This product will	
	however readily support combustion.	

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: KEROSINE - UNSPECIFIED - KEROSINE (PETROLEUM), HYDRODESULPHURIZED

Page: 2

206 STRIKE RELEASE OIL

Section 4: First aid measures

4.1. Description of first aid measures Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor. Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor. Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor. Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor. 4.2. Most important symptoms and effects, both acute and delayed Skin contact: There may be irritation and redness at the site of contact. Eye contact: There may be irritation and redness. The eyes may water profusely. Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting. Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. 4.3. Indication of any immediate medical attention and special treatment needed Section 5: Fire-fighting measures

societien er i ne righting medeal

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside keep bystanders upwind and away from danger point. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

206 STRIKE RELEASE OIL

Page: 4

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. The floor of the storage room must be
	impermeable to prevent the escape of liquids.
Respiratory protection:	Gas/vapour filter, type A: organic vapours (EN141). and must be worn if vapour
	concentration exceeds WEL
Hand protection:	Impermeable gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Colourless		
Odour:	Aromatic		
Evaporation rate:	Moderate		
Solubility in water:	Not miscible		
Viscosity:	Non-viscous		
Boiling point/range°C:	140 - 250	Flash point°C:	38
Autoflammability°C:	~240	Relative density:	0.81
pH:	n/a		

206 STRIKE RELEASE OIL

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for substance:

Hazard	Route	Basis
Aspiration hazard	-	Based on test data

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

Page: 5

206 STRIKE RELEASE OIL

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1223

14.2. UN proper shipping name

Shipping name: KEROSENE

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

206 STRIKE RELEASE OIL

	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and 3:	H226: Flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	R10: Flammable.
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.
	R65: Harmful: may cause lung damage if swallowed.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.

Page: 7