

Contract Medium Carpet Protection Film - Clear

READYFIX PRODUCT CODES: Z750-128 | Z750-129



An economical, self-adhesive clear polythene film for temporary protection of carpets during construction, decorating, refurbishment and maintenance work. The 60 micron film helps protect against dust, dirt, debris, foot traffic and accidental spillages, without requiring separate fixing tape.

- Clear finish keeps the covered carpet visible during use.
- Lightweight, waterproof film with good resistance to tearing and puncturing.

Readyfix range

Product code	Roll size	Nominal thickness	Coverage
Z750-128	600 mm x 100 m	60 micron (0.060 mm)	60 m ²
Z750-129	1200 mm x 100 m	60 micron (0.060 mm)	120 m ²

Technical specification

Property	Specification	Property	Specification
Film	Self-adhesive polyethylene	Colour	Clear
Thickness	60 micron nominal	Roll length	100 m
Width options	600 mm / 1200 mm	Finish	Smooth clear film
Water resistance	Waterproof film	Pack quantity	1 roll
Application	Temporary carpet protection	Fire performance	Non-flame-retardant

Application and removal

Vacuum the carpet and ensure it is clean, sound and completely dry. Test a small inconspicuous area first. Apply the adhesive face to the carpet, unroll in a straight line and smooth out firmly to remove air pockets and wrinkles. Overlap adjoining runs where required. Remove slowly and evenly as soon as the work is complete.

Limitations and safety

For carpeted surfaces only - do not apply to hard flooring. Test before use on delicate, wool, natural-fibre or recently fitted carpets. Do not use with active underfloor heating. The surface may become slippery when wet; clean spillages immediately and replace damaged film. Keep away from flames and ignition sources. Remove within 40 days unless the roll label specifies a shorter maximum application period.

Store in the original packaging in a cool, dry place away from direct sunlight and heat. Product image is illustrative. Equivalent products may be sourced from approved manufacturers, so packaging and appearance may vary. Dimensions, thickness and coverage are nominal; confirm critical requirements before ordering.