

EVERBUILD ONE STRIKE FILLER CARTRIDGE

Colour	Product Code	Pack Size	Box Qty
White	ONEC3	C3	12

Product Description

EVERBUILD ONE STRIKE is a revolutionary ready-mixed lightweight filler for the preparation of numerous surfaces prior to painting or wallpapering. Based on high strength lightweight polymeric fillers, the product outperforms conventional fillers in most applications. Designed for professional and D.I.Y use.

Benefits

- Fills in one go- No need to build up layers of filler.
- Easy to use - lightweight paste is incredibly easy to apply.
- No sanding required - finishes to a smooth surface.
- No sagging - the lightweight properties of ONE STRIKE prevent sagging even on ceilings.
- Non-shrink - will not shrink back whilst drying.
- Quick drying - ready to paint/paper in just 30 minutes.
- Overpaintable with most solvent based and emulsion paints.
- Overstainable
- Internal/external use.
- Dries brilliant white.

Areas For Use

Fills gaps and holes in:

- Plaster
- Brick
- Stone
- Wood
- Render

Limitations

- Do not use to fill plastic or metals.
- Do not apply when rain is imminent (external use).
- Do not apply in temperatures (ambient and surface) below 5°C.
- If using externally overpainting is essential.

Surface Preparation

All surfaces must be clean, dry and free from dust, grease and other contamination.

Application

Apply direct from tub with spatula/spreader. Smooth over surface and allow to dry. Sanding is not normally required although the product may be sanded if required. ONE STRIKE can be painted over after approx 30 minutes using water based paints. Leave to dry for 12 hours when using solvent based paints.

Specific Data

Appearance	Lightweight brilliant white paste
S.G. at 20°C	0.49-0.53gcm ³ (approx)
Movement Accommodation	Low / moderate
Maximum Fill	75mm in one coat -further layers may be built up
Maximum Width	50mm
Application Temperature	5°C to 30°C.
Drying Time	30 minutes at 20°C 50% R.H.
pH	8.9-9.9

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store at moderate temperatures.

Shelf Life

24 months from date of manufacture when stored according to manufacturers instructions.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.